

DOM Series

AE/DOM-OP; AE/DOM-OP230; AE/DOM-230B;
AE/DOM-OP12; AE/DOM-CO



Optical Smoke detector, with 9 Vdc Battery, AE/DOM-OP

Detector powered by included 9 Vdc alkaline battery. Optical smoke detector that is particularly effective with slow fires and without any flames. Acoustic alarm indication > 85dB at three metres. Luminous alarm indication. Manual operational test button. Fault signal in case of dirty or faulty detector. Size: 102-mm diameter, 40-mm height. Complies with the requirements of EN14604 and manufactured in accordance with ISO9001:2000 procedures. Adaptable to surface-mounted bas AE/C5-ZA

Optical Smoke Detector, 230 Vac, with Relay, AE/DOM-OP230

230 Vac detector, with normally open relay contact output. Optical smoke detector that is particularly effective with slow fires and without any flames. Acoustic alarm indication > 85dB at three metres. Luminous alarm indication. Manual operational test button. Fault signal in case of dirty or faulty detector. Size: 102-mm diameter, 40-mm height. Complies with the requirements of EN14604 and manufactured in accordance with ISO9001:2000 procedures. Adaptable to surface-mounted bas AE/C5-ZA

Optical Smoke Detector, 230 Vac, with Relay/Battery, AE/DOM-OP230B

230 Vac detector, with 9 Vdc alkaline battery and normally open relay contact output included. Optical smoke detector that is particularly effective with slow fires and without any flames. Acoustic alarm indication > 85dB at three metres. Luminous alarm indication. Manual operational test button. Fault signal in case of dirty or faulty detector. Size: 102-mm diameter, 40-mm height. Complies with the requirements of EN14604 and manufactured in accordance with ISO9001:2000 procedures. Adaptable to surface-mounted bas AE/C5-ZA

Optical Smoke Detector, 12 Vdc, with Relay, AE/DOM-OP12

12 Vdc detector. With normally open relay contact output. Optical smoke detector that is particularly effective with slow fires and without any flames. Acoustic alarm indication > 85dB at three metres. Luminous alarm indication. Manual operational test button. Fault signal in case of dirty or faulty detector. Size: 102-mm diameter, 40-mm height. Complies with the requirements of EN14604 and manufactured in accordance with ISO9001:2000 procedures. Adaptable to surface-mounted bas AE/C5-ZA

AE/DOM-OP; AE/DOM-OP230; AE/DOM-230B; AE/DOM-OP12; AE/DOM-CO