

Batteries Consisting of 67L Bottles (in single row) for HFC227ea

AEX/SBFM267 - AEX/SBFM1467



Description

High-pressure batteries made up of 67 and 80-litre bottles. Manufactured from non-welded, heat-treated steel (in accordance with Instruction MIE AP7 for pressurised vessels and European Directive 84/525/EEC).

Operating pressure:

42 bar, test pressure: 250 bar, service temperature: -10°C to +60°C.

Printed and painted in accordance with legislation.

Fitted with 1-inch AE-100 main valve, with pneumatic aperture through the head, non-return valves, together with hoses for pneumatic trip operation and discharge. Mounted on a metal frame with double securing fittings and discharge manifold with coupling thread to the installation.

The frames may be formed by mounting the bottles in a single row and a special frame for double row mounting.

Remarks:

A. Up to twelve bottles, the pneumatic battery trip is carried out by converting one of the bottles into pilot bottle, which requires one of the bottles to be fitted with an automatic trip coil and manual trip lever.

B. From 13 bottles, the batteries are fitted with two pilot trip bottles.

C. The cost of the trip systems described at points A and B has been included in the battery prices.

D. In the case in which directional valves are employed in the installation, it will be necessary to add a small 4.7-litre pilot bottle (see price).

REFERENCIA	Nº BOT.	CAP.(L)	CARGA MAX. (Kg)	DIMENSIONES
AEX/SBFM267	2	134	154	1,24x0,35x2,34
AEX/SBFM367	3	201	231	1,58x0,35x2,34
AEX/SBFM467	4	268	308	1,92x0,35x2,34
AEX/SBFM567	5	335	385	2,26x0,35x2,34
AEX/SBFM667	6	402	462	2,6x0,35x2,34
AEX/SBFM767	7	469	539	2,94x0,35x2,34
AEX/SBFM867	8	536	616	3,28x0,35x2,34
AEX/SBFM967	9	603	693	3,62x0,35x2,34
AEX/SBFM1067	10	670	770	3,96x0,35x2,34
AEX/SBFM1167	11	737	847	4,3x0,35x2,34
AEX/SBFM1267	12	804	924	4,64x0,35x2,34
AEX/SBFM1367	13	871	1001	4,98x0,35x2,34
AEX/SBFM1467	14	938	1078	5,32x0,35x2,34