

Batteries Consisting of 67L Bottles (in double row) for CO2

AEX/SBCO367D - AEX/SBCO2067D

Description

High-pressure batteries made up of 67 and 80-litre bottles. Manufactured from non-welded, heat-treated steel (in accordance with Instruction MIE AP7 for pressurised vessels and European Directive 84/525/EEC).

Operating pressure:

60 bar, test pressure: 250 bar, service temperature: -10°C to +60°C.

Printed and painted in accordance with legislation.

Fitted with 1-inch AE-100 main valve, with pneumatic aperture through the head, non-return valves, together with hoses for pneumatic trip operation and discharge. Mounted on a metal frame with double securing fittings and discharge manifold with coupling thread to the installation.

The frames may be formed by mounting the bottles in a single row and a special frame for double row mounting.

Remarks:

A. Up to twelve bottles, the pneumatic battery trip is carried out by converting one of the bottles into pilot bottle, which requires one of the bottles to be fitted with an automatic trip coil and manual trip lever.

B. From 13 bottles, the batteries are fitted with two pilot trip bottles.

C. The cost of the trip systems described at points A and B has been included in the battery prices.

D. In the case in which directional valves are employed in the installation, it will be necessary to add a small 4.7-litre pilot bottle (see price).



REFERENCIA	Nº BOT.	CAP.(L)	CARGA MAX.(Kg)	DIMENSIONES
AEX/SBCO367D	3	201	135	1,25x0,76x2,2
AEX/SBCO467D	4	268	180	1,25x0,76x2,2
AEX/SBCO567D	5	335	225	1,59x0,76x2,2
AEX/SBCO667D	6	402	270	1,59x0,76x2,2
AEX/SBCO767D	7	469	315	1,93x0,76x2,2
AEX/SBCO867D	8	536	360	1,93x0,76x2,2
AEX/SBCO967D	9	603	405	2,27x0,76x2,2
AEX/SBCO1067D	10	670	450	2,27x0,76x2,2
AEX/SBCO1167D	11	737	495	2,61x0,76x2,2
AEX/SBCO1267D	12	804	540	2,61x0,76x2,2
AEX/SBCO1367D	13	871	585	2,95x0,76x2,2
AEX/SBCO1467D	14	938	630	2,95x0,76x2,2
AEX/SBCO1567D	15	1.005	675	3,29x0,76x2,2
AEX/SBCO1667D	16	1.072	720	3,29x0,76x2,2
AEX/SBCO1767D	17	1.139	765	3,63x0,76x2,2
AEX/SBCO1867D	18	1.206	810	3,63x0,76x2,2
AEX/SBCO1967D	19	1.273	855	3,97x0,76x2,2
AEX/SBCO2067D	20	1.340	900	3,97x0,76x2,2