

TITANUS PRO·SENS®

AETP

Description

TITANUS PRO·SENS® is a universal air sampling device for a broad range of applications.

The high degree of modularity of the device makes it possible to achieve a cost-effective solution – customised to suit the specific needs of the customer.

An additional price advantage comes with the optional equipping of the device with a second detector module. This means that one air sampling device can monitor two separate monitored areas. Alternatively, doubleknock detection can be set up for both room and equipment monitoring purposes.

TITANUS PRO·SENS® is available with 1 to 3 alarm levels, with a network option, in the cold storage version or in the silent version, which operates at noise levels as low as 23 dB (A).

The coverage of the detector is in accordance with EN 5420: a single TITANUS PRO·SENS® 2 system can replace up to 64 point-type smoke detectors. Thanks to a powerful fan operating at up to 560 Pa, a pipe length of up to 560 m can be achieved fulfilling EN 5420 Class A to C requirement.



Applications

The robust TITANUS PRO·SENS® offers a comprehensive product range complete with accessories approved to EN 5420. This allows the device to be used in areas where other smoke detectors and air sampling smoke detection systems have long reached their limits.

These include:

- It areas and clean rooms.
- General warehouses, high bay storage areas and cold storage areas
- Wind farms.
- Libraries, museums and archives.
- Hospitals, hotel rooms and saunas.
- Recycling areas.
- Rail vehicles and tunnels.

Advantages

- Early fire detection thanks to innovative, highly sensitive HPLS light source technology.
- High degree of false alarm immunity through LOGIC·SENS fire pattern recognition
- 3 seuils d'alarme pour un concept d'alarme échelonné.
- Up to 3 alarm thresholds for a tiered alarm concept.
- A broad range of accessories, approved to EN 5420.
- High degree of modularity for a customised, cost effective solution.
- Reliable project design with just 5 mouse clicks.
- Time saving commissioning through Plug & Play.
- Doubleknock detection to enable separate room and equipment monitoring.
- Available as silent option from 23 dB (A).

TECHNICAL CHARACTERISTICS		
Basic equipment	TITANUS PROSENS	TITANUS PROSENS 2
Number of detector modules	1	2
Max. number of sampling orifices	32	64
Max. pipe length	300m	560m
Monitored area per sampling hole	Corresponds to one point-type smoke detector in accordance with VDE 0833-2	
Monitoring of pipe systems for breakage and obstruction	Optional adjustment for individual hole monitoring **	
Double-knock detection	Possible using detector box	Yes (separate room and equipment protection)
Sensitivity detector module DM-Tx-01 (Sampling holes in accordance with EN 54-20: Class A max. 2 x 32, Class B max. 2 x 32, Class C max. 2 x 32)	Info-alarm: 0.005 % LT/m* Pre-alarm: 0.010 % LT/m* Main alarm: 0.015 % LT/m	
Sensitivity detector module DM-Tx-10(Sampling holes in accordance with EN 54-20: Class A max. 2 x 9, Class B max. 2 x 32, Class C max. 2 x 32)	Info-alarm: 0.03 % LT/m* Pre-alarm: 0.07 % LT/m* Main alarm: 0.1 % LT/m	
Sensitivity detector module DM-Tx-50 (Sampling holes in accordance with EN 54-20: Class A max. 2 x 4, Class B max. 2 x 12, Class C max. 2 x 32)	Info-alarm: 0.17 % LT/m* Pre-alarm: 0.3 % LT/m* Main alarm: 0.5 % LT/m	
Alarms (potential free change-over contacts)	Up to 3 alarms per detector module (info-alarm, pre-alarm and main alarm)	

TITANUS PRO·SENS®

AETP

TECHNICAL CHARACTERISTICS		
Fault alarms	Detección común (1 contacto libre de tensión por módulo de detección, NC o NA)	
Alarm and fault relay power rating	1A, 30 Vcc, máx. 24W	
Clamped connections	máx. 1,5 mm ²	
Displays on device: - Main alarm (Types TP-1/a, TP-3, TP-4, TP-5) - Pre-alarm (Types TP-4, TP-5) - Info-alarm (Type TP-5) - Fault - Operation	1 red alarm indicator per detector module 1 red alarm indicator per detector module* 1 red alarm indicator per detector module* Yellow collective fault Green operation display	
Operating voltage	24 Vcc (14-30Vcc)	
Max. quiescent current (at 24 V DC)***	200 (210) mA*	220 (240) mA*
Max. alarm current (at 24 V DC)***	210 (220) mA*	240 (250) mA*
Starting current limited to	300 (390) mA	320 (400) mA
SL version: Max. quiescent current (at 24 V DC)*** Max. current consumption alarm (at 24 V DC)*** Starting current limited to	150 (140) mA* 160 (150) mA* 300 (230) mA*	180 (170) mA* 190 (180) mA* 330 (260) mA*
Noise level (with sound damper)	from 23 dB (A)	
Dimensions (W x H x D)	200 x 292 x 113 mm	
Weight	1460g	1560g
Protection category	IP 20 (IP 52 optional)	
Temperature range - Cold storage option (no SL version)	-20 °C a + 60 °C -40 °C a + 60 °C	
Humidity (permanent)	10 % bis 95 % relative humidity	
Event log	Built-in, additional external data storage possible	
Connection of external alarm notifications	Parallel display optional	
Network capability	optional ethernet network version****	
Approved in accordance with EN 54-20, Classes A, B, C: VDS n° BPRI n	G 202064 0786-CPD-20685	

* Depending on type of device

** Depending on project design

*** At standard 6.9 V fan voltage

**** Version TITANUS PRO·SENS® /net