

CONVENTIONAL SIREN WITH OUTDOOR SPOTLIGHT IP66 AE/V-ASF23WP

Description

Acoustic siren with low consumption spotlight for outdoor use certified EN54: 3 and EN54: 23. IP66 rated.

The siren can be configured as optical-acoustic (flash + sound) or optical only (flash). 2 sound levels can be configured as required. The installation must be connected in accordance with the requirements of the UNE 23007-14: 2014 standard.



TECHNICAL CHARACTERISTICS

Supply voltage:	18 ~ 27V.
Wiring:	2 wires. Recommended section AWG 18 (IEC 1mm ²)
Class:	WO Wall
Alarm consumption	<ul style="list-style-type: none"> • flash only 6.5 mA • flash + low volume 8.7 mA • flash + high volume 11 mA
Sound intensity:	<ul style="list-style-type: none"> • high volume 99 ± 3 dB (A) • low volume 89 ± 3 dB (A)
Flash frequency:	0.5 Hz Flash pulse duration: 60 msg
Temperature range:	-25° - + 70° C (room temperature)
Humidity range:	Relative humidity 10% - 90% non-condensing
Shell material:	ABS FR V0 red
IP degree of protection:	IP66
Dimensions:	110 mm x 110 mm x 100 mm.
Weight:	290g

CERTIFICATIONS

EN54-3/EN54-23: 0359/CPR/00419